

## STPG370

呼び径		外径Φ		厚	kg/m
B	A				
1/8	6A	10.5	Sch40	1.7	0.369
1/8	6A	10.5	Sch50	2.2	0.450
1/8	6A	10.5	Sch60	2.4	0.479
1/4	8A	13.85	Sch40	2.2	0.629
1/4	8A	13.85	Sch50	2.4	0.675
1/4	8A	13.85	Sch60	3	0.799
3/8	10A	17.3	Sch40	2.3	0.851
3/8	10A	17.3	Sch50	2.8	1.00
3/8	10A	17.3	Sch60	3.2	1.11
1/2	15A	21.7	Sch40	2.8	1.31
1/2	15A	21.7	Sch50	3.2	1.46
1/2	15A	21.7	Sch60	3.7	1.64
3/4	20A	27.2	Sch40	2.9	1.74
3/4	20A	27.2	Sch50	3.4	2.00
3/4	20A	27.2	Sch60	3.9	2.24
1	25A	34	Sch40	3.4	2.57
1	25A	34	Sch50	3.9	2.89
1	25A	34	Sch60	4.5	3.27
1・1/4	32A	42.7	Sch40	3.6	3.47
1・1/4	32A	42.7	Sch50	4.5	4.24
1・1/4	32A	42.7	Sch60	4.9	4.57
1・1/2	40A	48.6	Sch40	3.7	4.1
1・1/2	40A	48.6	Sch50	4.5	4.89
1・1/2	40A	48.6	Sch60	5.1	5.47
2	50A	60.5	Sch20	3.2	4.52
2	50A	60.5	Sch40	3.9	5.44
2	50A	60.5	Sch50	4.9	6.72
2	50A	60.5	Sch60	5.5	7.46
2・1/2	65A	76.3	Sch20	4.5	7.97
2・1/2	65A	76.3	Sch40	5.2	9.12
2・1/2	65A	76.3	Sch50	6	10.4
2・1/2	65A	76.3	Sch60	7	12
3	80A	89.1	Sch20	4.5	9.39
3	80A	89.1	Sch40	5.5	11.3
3	80A	89.1	Sch50	6.6	13.4
3	80A	89.1	Sch60	7.6	15.3
3・1/2	90A	101.6	Sch20	4.5	10.8
3・1/2	90A	101.6	Sch40	5.7	13.5
3・1/2	90A	101.6	Sch50	7	16.3
3・1/2	90A	101.6	Sch60	8.1	18.7
4	100A	114.3	Sch20	4.9	13.2
4	100A	114.3	Sch40	6	16
4	100A	114.3	Sch50	7.1	18.8
4	100A	114.3	Sch60	8.6	22.4
5	125A	139.8	Sch20	5.1	16.9
5	125A	139.8	Sch40	6.6	21.7
5	125A	139.8	Sch50	8.1	26.3
5	125A	139.8	Sch60	9.5	30.5
6	150A	165.2	Sch20	5.5	21.7
6	150A	165.2	Sch40	7.1	27.7
6	150A	165.2	Sch50	9.3	35.8
6	150A	165.2	Sch60	11	41.8

呼び径		外径Φ		厚	kg/m
B	A				
8	200A	216.3	Sch20	6.4	33.1
8	200A	216.3	Sch30	7	36.1
8	200A	216.3	Sch40	8.2	42.1
8	200A	216.3	Sch50	10.3	52.3
8	200A	216.3	Sch60	12.7	63.8
10	250A	267.4	Sch20	6.4	41.2
10	250A	267.4	Sch30	7.8	49.9
10	250A	267.4	Sch40	9.3	59.2
10	250A	267.4	Sch50	12.7	79.8
10	250A	267.4	Sch60	15.1	93.9
12	300A	318.5	Sch20	6.4	49.3
12	300A	318.5	Sch30	8.4	64.2
12	300A	318.5	Sch40	10.3	78.3
12	300A	318.5	Sch50	14.3	107
12	300A	318.5	Sch60	17.4	129
14	350A	355.6	Sch10	6.4	55.1
14	350A	355.6	Sch20	7.9	67.7
14	350A	355.6	Sch30	9.5	81.1
14	350A	355.6	Sch40	11.1	94.3
14	350A	355.6	Sch50	15.1	127
14	350A	355.6	Sch60	19	158
16	400A	406.4	Sch10	6.4	63.1
16	400A	406.4	Sch20	7.9	77.6
16	400A	406.4	Sch30	9.5	93
16	400A	406.4	Sch40	12.7	123
16	400A	406.4	Sch50	16.7	160
16	400A	406.4	Sch60	21.4	203
18	450A	457.2	Sch10	6.4	71.1
18	450A	457.2	Sch20	7.9	87.5
18	450A	457.2	Sch30	11.1	122
18	450A	457.2	Sch40	14.3	156
18	450A	457.2	Sch50	19	205
18	450A	457.2	Sch60	23.8	254
20	500A	508	Sch10	6.4	79.2
20	500A	508	Sch20	9.5	117
20	500A	508	Sch30	12.7	155
20	500A	508	Sch40	15.1	184
20	500A	508	Sch50	20.6	248
20	500A	508	Sch60	26.2	311
22	550A	558.8	Sch10	6.4	87.2
22	550A	558.8	Sch20	9.5	129
22	550A	558.8	Sch30	12.7	171
22	550A	558.8	Sch40	15.9	213
24	600A	609.6	Sch10	6.4	92.5
24	600A	609.6	Sch20	9.5	141
24	600A	609.6	Sch30	14.3	210
26	650A	660.4	Sch10	7.9	127
26	650A	660.4	Sch20	12.7	203

〒660-0805  
 尼崎市西長洲町2-4-5  
 TEL06-6482-3051  
 FAX06-6482-3054

